

FL 630 SUPER - Especificaciones técnicas



Description

FL 630 SUPER es un neumático del flotación particularmente idóneo para utilizarlo con remolques, auto cisternas y pulverizadores. Su estructura resistente proporciona una excelente tracción y un agarre perfecto incluso en las curvas y durante las maniobras. El particular dibujo de la banda de rodadura garantiza una perfecta adherencia en cualquier tipo de terreno, así como avanzadas propiedades de auto-limpieza. FL 630 SUPER permite velocidades hasta 70 km/h.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

Version	HD
Type	TL
Tyre Size	600/55 R 26.5
LI/SS	177 D

Dimensions US Standard

Usa code	94048946
Section Width (inch)	24.1
Overall Diameter (inch)	52.5
Static Loaded Radius (inch)	23.8
Rolling Circumference (inch)	161.6
Rim Rec	AG 20.00
ECE	E11-106R-003005

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58	73	87
40	4020	4990	5960	7240	8380	9660	10950	11750	13040	14330	15130	16090
30	4870	6040	7210	8770	10130	11690	13250	14220	15780	17340	18310	19480
25	5480	6790	8100	9850	11390	13140	14890	15980	17740	19490	20580	21890
20	6080	7540	8990	10950	12640	14580	16530	17750	19700	21640	22850	24300
15	6360	7890	9410	11450	12320	15270	17290	18570	20600	22640	23910	25430
5	7240	8980	10720	13040	15070	17380	19710	21150	23470	25780	27240	28970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 2:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..