

FL 630 SUPER - Especificaciones técnicas



Description

FL 630 SUPER es un neumático del flotación particularmente idóneo para utilizarlo con remolques, auto cisternas y pulverizadores. Su estructura resistente proporciona una excelente tracción y un agarre perfecto incluso en las curvas y durante las maniobras. El particular dibujo de la banda de rodadura garantiza una perfecta adherencia en cualquier tipo de terreno, así como avanzadas propiedades de auto-limpieza. FL 630 SUPER permite velocidades hasta 70 km/h.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	710/50 R 26.5
LI/SS	170 D

Dimensions International Standard

Section Width (mm)	727
Overall Diameter (mm)	1383
Static Loaded Radius (mm)	626
Rolling Circumference (mm)	4237
SRI (mm)	650
Rim Rec	AG 24.00
Rim Alt	AG 20.00
ECE	E11-106R-003009

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1745	2020	2290	2780	3220	3710	4200	4525	5015	5450
65	1920	2220	2520	3060	3540	4080	4620	4980	5520	6000
50	2325	2690	3050	3705	4285	4940	5595	6030	6680	7260
40	2615	3025	3430	4165	4815	5550	6285	6775	7510	8160
25	3035	3510	3985	4835	5595	6450	7300	7870	8725	9480
10	3460	4000	4540	5510	6375	7345	8320	8965	9940	10800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 12:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..