

FL 637 - Ficha técnica



Description

FL 637 es un neumático radial Flotation específico para esparcidores, remolques y cisternas. La estructura de la banda de rodadura con cinturón de acero garantiza una mayor durabilidad y capacidad de carga más elevada. Además de las excelentes propiedades de flotación que se traducen en reducida compactación del suelo, este neumático muestra extraordinarias propiedades de auto-limpieza. El diseño direccional de la banda de rodadura asegura una excepcional tracción permitiendo velocidades hasta 70 km/h.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
520/50 R 17	STANDARD	94054909	151D/148E	16.00		20.3	37.5	16.3	115.4	TL	E11-106R-004070
560/45 R 22.5	STANDARD	94074174	160D	AG 16.00		21.4	42.4	19.7	130.9	TL	E11-106R-008660

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..