

FL 639 - Especificaciones técnicas



Description

FL 639 es un neumático de flotación empleado principalmente en el campo idóneo para aplicaciones con pulverizadores. Su ancha huella garantiza una reducida compactación del suelo, favoreciendo una mayor productividad de los cultivos. La banda de rodadura reforzada y la protección del flanco contribuyen a un ciclo de vida más largo. FL 639 asegura una excelente tracción además de optimas propiedades de auto-limpieza.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor

Version	STANDARD
Type	TL
Tyre Size	710/40 R 22.5
LI/SS	170 B/158 B
LI/SS DRIVE WHEEL	158 B
LI/SS FREE ROLLING	170 B

Dimensions US Standard

Usa code	94063246
Section Width (inch)	28.6
Overall Diameter (inch)	44.9
Static Loaded Radius (inch)	19.8
Rolling Circumference (inch)	137.5
Rim Rec	AG 24.00
ECE	E11-106R-006479

Load capacity (lbs)

mph / psi	12	15	17	20	23	26	29	32	35	38	41	44	46
30 FR	5080	5840	6600	7325	8050	8700	9350	10025	10700	11500	12300	12750	13200
30 DW	3640	4160	4680	5180	5680	6140	6600	7100	7600	8200	8800	9075	9350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 15:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..