

FLOTATION 351 - Especificaciones técnicas



Description

FLOTATION 351 es un neumático diagonal de flotación ideal para aplicaciones de transporte con remolques. Los tacos extra profundos suministran una extraordinaria tracción y prolongan la vida del neumático. FLOTATION 351 es el neumático ideal para las superficies mojadas y húmedas que asegura una elevada capacidad de carga.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Remolque

Version	STANDARD
Type	TL
Tyre Size	48 X 31.00 - 20
LI/SS	148 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	775
Overall Diameter (mm)	1283
Static Loaded Radius (mm)	559
Rolling Circumference (mm)	3886
Rim Rec	26.00 HF
Rim Alt	26.00 VF
ECE	E11-106R-004385
TRA Code	HF3

Load capacity (Kg)

km/h / bar	2.70
50	3150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 7:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..