

FLOTATION 647 - Especificaciones técnicas



Description

FLOTATION 647 es un neumático para la maquinaria agrícola que se distingue por una excelente tracción en los terrenos blandos y en los pastos. Además de las elevadas propiedades de auto limpieza, el particular dibujo de la banda de rodadura ofrece una amplia área de contacto que proporciona una distribución uniforme del peso y prestaciones excelentes en el terreno blando.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricultura: Maquinaria agrícola

Version	STANDARD
Type	TL
Tyre Size	520/50 - 17
LI/SS DRIVE WHEEL	147 B
LI/SS FREE ROLLING	159 B

Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	965
Static Loaded Radius (mm)	426
Rolling Circumference (mm)	2907
Rim Rec	AG 16.00
ECE	E11-106R-005770

Load capacity (Kg)

km/h / bar	4.00
50 FR	4375
50 DW	3075

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 14:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..