

FLOTATION 648 - Especificaciones técnicas



Description

FLOTATION 648 es particularmente idóneo para las operaciones de transporte en el campo y por la carretera, así como para aplicaciones con pulverizadores. Algunas medidas son idóneas para cosechadoras y prensas para empacar la paja. El particular dibujo de la banda de rodadura permite transportar cargas muy pesadas con bajas presiones, garantizando consecuentemente una compactación reducida del suelo y protegiendo al mismo tiempo los cultivos de daños.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora •
Esparcidor

Version	STANDARD
Type	TL
Tyre Size	500/60 - 22.5
LI/SS DRIVE WHEEL	145 A8/142 B
LI/SS FREE ROLLING	157 A8/154 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	500
Overall Diameter (mm)	1170
Static Loaded Radius (mm)	510
Rolling Circumference (mm)	3489
Rim Rec	AG 16.00
Rim Alt	15.00 ; 17.00
ECE	E11-106R-004552

Load capacity (Kg)

km/h / bar	1.50	2.00	2.40
10 FR	4390	5195	5775
20 FR	3950	4675	5200
30 FR	3510	4155	4620
40 FR	3135	3710	4125
50 FR	2820	3340	3750
10 DW	3085	3645	4060
20 DW	2780	3280	3655
30 DW	2470	2920	3250
40 DW	2205	2605	2900
50 DW	1985	2345	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 21:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..