

FLOTATION 648 - Especificaciones técnicas



Description

FLOTATION 648 es particularmente idóneo para las operaciones de transporte en el campo y por la carretera, así como para aplicaciones con pulverizadores. Algunas medidas son idóneas para cosechadoras y prensas para empacar la paja. El particular dibujo de la banda de rodadura permite transportar cargas muy pesadas con bajas presiones, garantizando consecuentemente una compactación reducida del suelo y protegiendo al mismo tiempo los cultivos de daños.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora •
Esparcidor

Version	STANDARD
Type	TL
Tyre Size	700/50 - 22.5
LI/SS DRIVE WHEEL	156 A8/153 B
LI/SS FREE ROLLING	168 A8/164 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	700
Overall Diameter (mm)	1270
Static Loaded Radius (mm)	550
Rolling Circumference (mm)	3775
Rim Rec	24.00
ECE	E4-106R-002270

Load capacity (Kg)

km/h / bar	1.50	1.60	1.80
10 FR	7050	7315	7840
20 FR	6345	6585	7055
30 FR	5640	5850	6270
40 FR	5035	5225	5600
50 FR	4530	4705	5000
10 DW	5035	5230	5600
20 DW	4530	4705	5040
30 DW	4025	4185	4480
40 DW	3595	3735	4000
50 DW	3235	3360	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 12:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..