



## FORESTECH - Especificaciones técnicas



### Description

FORESTECH es un neumático BKT con cinturones de acero, idóneo para trabajar en el sector forestal con máquinas **forwarder** (autocargadores). Este neumático ofrece una excelente tracción incluso en condiciones pesadas. Su robusto talón y el área del hombro reforzada aseguran una elevada resistencia a las perforaciones y una vida más larga del neumático. De esta forma se podrán llevar a cabo sin preocupaciones las operaciones forestales más exigentes y difíciles.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agricultura: Autocargadora

Version	STEEL BELTED
Type	TL
Tyre Size	600/55 - 26.5
LI/SS	165 A8/172 A2

## Dimensions US Standard

Usa code	94031238
Ply Rating	20
Section Width (inch)	24
Overall Diameter (inch)	52.6
Static Loaded Radius (inch)	24.3
Rolling Circumference (inch)	158.7
Rim Rec	AG 20.00
ECE	E11-106R-003419
TRA Code	LS2

## Load capacity (lbs)

mph / psi	73
25	11350
20	12150
5	13890

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..