

GR 288 - Especificaciones técnicas



Description

GR 288 (G-2/L-2) es un neumático versátil con una carcasa diagonal para las niveladoras o las cargadoras. Este neumático es ideal para utilizarlo en el sector de la construcción, la preparación del terreno y en la construcción de carreteras, así como en otros ambientes blandos o fangosos. El dibujo de la banda de rodadura posee óptimas propiedades de auto-limpieza que se traducen en una excelente tracción. Gracias a su mezcla especial, resistente a los cortes y los desgarros, este neumático asegura un amplio ciclo de vida.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Buldócer • Pala cargadora
OTR: Motoniveladora

Version	STANDARD
Type	TL
Tyre Size	23.5 - 25

Dimensions US Standard

Usa code	94014453
Ply Rating	16
Overall Width (inch)	23.4
Overall Diameter (inch)	63.4
Static Loaded Radius (inch)	27.9
Rolling Circumference (inch)	188.3
Rim Rec	19.50/2.5
ECE	E11-106R-005406
TRA Code	G2/L2
Tread Depth	38

Load capacity (lbs)

mph / psi	29	44
25	10500	-
5	-	20900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 5:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..