

JUMBO TRAX HD - Especificaciones técnicas



Description

JUMBO TRAX HD es un neumático con un dibujo de bloques en la banda de rodadura para las minicargadoras. Este neumático se caracteriza por su particular resistencia a los cortes y los desgarros y es particularmente idóneo para los trabajos más pesados. Su banda de rodadura profunda, así como la excelente protección de los flancos garantizan un amplio ciclo de vida del neumático. JUMBO TRAX HD también está disponible en versión "special" (especial).

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Minicargadora compacta

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	325
Overall Diameter (mm)	855
Static Loaded Radius (mm)	387
Rolling Circumference (mm)	2522
Rim Rec	9.75
ECE	E11-106R-005563

Load capacity (Kg)

km/h / bar	4.50
10	2540
15	2005
25	1855

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 8:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..