

LG 408 - Especificaciones técnicas



Description

LG 408 es un neumático para el césped y la jardinería, idóneo para segadoras y minitractores. El específico dibujo de la banda de rodadura hace que este neumático sea delicado en el terreno, previniendo daños al prado facilitando al mismo tiempo la manipulación y las maniobras. LG 408 está disponible en una versión "aramid belted", con cinturones de aramida, para usuarios que requieren una mayor resistencia a la perforación.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Segadora • Minitractor

Version	ARAMID BELTED
Type	TL
Tyre Size	24 X 13.00 - 12

Dimensions US Standard

Usa code	94012909
Ply Rating	6
Section Width (inch)	12.8
Overall Diameter (inch)	24
Static Loaded Radius (inch)	10.6
Rolling Circumference (inch)	69.1
Rim Rec	10.5 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003364

Load capacity (lbs)

mph / psi	32
10	2390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 20:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..