

LIFTMAX LM 63 - Especificaciones técnicas



Description

El LIFTMAX LM 63 se ha desarrollado especialmente para operaciones industriales y de logística. El diseño de su banda de rodadura con 3 costillas ofrece una baja resistencia al rodamiento, un buen agarre en mojado y un desgaste uniforme, unidos a una mejor conducción. Se trata de un neumático radial All Steel con cinturones de acero multiestrato que proporciona una menor vibración, así como una estabilidad y un confort mejorados.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Cosechadora

Industrial: Tow Tractor • Remolque

Version	STANDARD
Type	TL
Tyre Size	6.00 R 9
LI/SS	121 A5

Dimensions International Standard

Overall Width (mm)	160
Overall Diameter (mm)	542
Rim Rec	4.00E

Load capacity (Kg)

km/h / bar	10
25	1450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 15:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..