

MAGLIFT PREMIUM - Especificaciones técnicas



Description

MAGLIFT PREMIUM es un neumático sólido particularmente desarrollado para operaciones de servicio pesado con carretillas elevadoras en el puerto, la minería o los astilleros de desguace. La banda de rodadura extra profunda (25% más en comparación con la versión estándar) con su diseño agresivo y robusto ofrece una excepcional tracción anterior y lateral así como un excelente control de la dirección. La mezcla especial de la banda de rodadura se traduce en una extraordinaria resistencia a los cortes y las laceraciones, prolongando la vida de lo neumático. Otras ventajas son la baja resistencia a la rodadura y una marcha suave.

UM

US Standard

Construction

◆ SOLID

Machinery

Industrial: Carretilla elevadora

Version	STANDARD
Type	
Tyre Size	6.50 - 10

Dimensions US Standard

Usa code	94055302
Section Width (inch)	5.9
Overall Diameter (inch)	22.9
Rim Rec	5.00 F - 10

Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	5160
15 STEER WHEEL	3970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 10:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..