



MP 585 - Ficha técnica



Description

MP 585 es un neumático agro-industrial idóneo para los vehículos polivalentes que se utilizan en el sector de la municipalidad/mantenimiento. Este neumático ha sido específicamente proyectado con un dibujo de bloques que ofrece la máxima estabilidad y durabilidad en las condiciones operativas más difíciles, incluso a altas velocidades.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Vehículo universal

Industrial: Vehículo universal

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.5 - 20	STANDARD	94038336		10	9	9 SDC	10.7	38.2	17.9	113.8	TL	E4-54R-0022631
12.5 - 20	STANDARD	94038404		12	11	12 SDC	13.2	41.3	18.9	123.2	TL	E4-54R-0022635
6.50 - 20	STANDARD	94051243	38 A8	10	5.50 F	4.00 E ; 5.00 F	7.9	34.4	0	0	TT	E11-106R-004308

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 5:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..