

MT 612 - Especificaciones técnicas



Description

MT 612 ha sido desarrollado para usos polivalentes tanto por carretera y como fuera de carretera. Su robusta carcasa permite transportar cargas pesadas a una alta velocidad, mientras que los tacos anchos aseguran una extraordinaria tracción. La banda de rodadura extra ancha garantiza excelentes propiedades de flotación sobre la arena y el barro.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Remolque

Industrial: Vehículo universal

Version	STANDARD
Type	TT
Tyre Size	16.0/70 - 20

Dimensions US Standard

Usa code	94035922
Ply Rating	16
Section Width (inch)	15.9
Overall Diameter (inch)	43.1
Static Loaded Radius (inch)	20.5
Rolling Circumference (inch)	131
Rim Rec	13.00 T

Load capacity (lbs)

mph / psi	65
50 LS	6780
50 LD	6010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 12:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..