

MULTIMAX MP 513 - Especificaciones técnicas



Description

MULTIMAX MP 513 ha sido proyectado por BKT para utilizarlo con vehículos polivalentes en el sector de la municipalidad/mantenimiento y de transporte para uso agrícola y industrial. El neumático es perfecto para vehículos universales y camiones de fertilizante. Gracias a su robusta carcasa de nylon reforzada con cinturones de acero, MULTIMAX MP 513 permite transportar cargas pesadas a altas velocidades proporcionando una experiencia de conducción confortable. Asegura una vida operativa más larga así como optimas propiedades de auto-limpieza.

UM

US Standard

Construction



RADIAL

Machinery

Agricultura: Vehículo universal • Camión de fertilizantes
Industrial: Vehículo universal

Version	STANDARD
Type	TL
Tyre Size	495/70 R 24 MPT
LI/SS	155 G

Dimensions US Standard

Usa code	94035908
Section Width (inch)	19.6
Overall Diameter (inch)	51.3
Static Loaded Radius (inch)	23.1
Rolling Circumference (inch)	156.5
Rim Rec	W 16 L
Rim Alt	DW 15 L ; DW 16 L ; W 15 L
ECE	E4-54R-0029057

Load capacity (lbs)

mph / psi	23	29	36	44	51
55	4360	5160	6260	7160	8550
40	4740	5600	6800	7780	9270
25	5030	5940	7210	8240	9830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 23:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..