

## MULTIMAX MP 515 - Especificaciones técnicas



### Description

MULTIMAX MP 515 es un neumático agro-industrial radial desarrollado para los vehículos universales y camiones de fertilizantes. Es idóneo para aplicaciones municipalidad y de transporte. El neumático muestra un diseño único de la banda de rodadura, que se traduce en un gran confort de conducción por carretera, así como excelentes propiedades de auto-limpieza y una excelente tracción. Su robusta carcasa de nylon con cinturones de acero y su hombro redondeado aseguran una elevada duración. MULTIMAX MP 515 es un neumático perfecto incluso a elevadas velocidades (90km/h).

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Vehículo universal • Camión de fertilizantes

|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 405/70 R 20 MPT |
| LI/SS     | 136 G           |

## Dimensions US Standard

|                              |                               |
|------------------------------|-------------------------------|
| Usa code                     | 94056545                      |
| Section Width (inch)         | 16                            |
| Overall Diameter (inch)      | 42.4                          |
| Static Loaded Radius (inch)  | 19.4                          |
| Rolling Circumference (inch) | 129.4                         |
| Rim Rec                      | 13                            |
| Rim Alt                      | 13 SDC ; 12 SDC ; 11 SDC ; 11 |
| ECE                          | E4-54R-0016565                |

## Load capacity (lbs)

| mph / psi | 23   | 29   | 36   | 44   | 51   |
|-----------|------|------|------|------|------|
| 55        | 2950 | 3480 | 4010 | 4500 | 4940 |
| 40        | 3210 | 3780 | 4350 | 4880 | 5370 |
| 25        | 3410 | 4010 | 4620 | 5180 | 5690 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 5:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..