

MULTIMAX MP 519 - Especificaciones técnicas



Description

MULTIMAX MP 519 es un neumático idóneo para camiones ligeros en todas las aplicaciones de transporte. La carcasa reforzada con cinturones de acero garantiza una excelente estabilidad a grandes velocidades (90 km/h). Gracias a la baja resistencia al rodamiento, el neumático asegura un consumo reducido de carburante.

UM

International Standard

Construction



RADIAL

Machinery

Industrial: Camión ligero

Version	STANDARD
Type	TL
Tyre Size	7.50 R 16 LT
LI/SS	112/110G

Dimensions International Standard

Ply Rating	8
Section Width (mm)	220
Overall Diameter (mm)	810
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2449
Rim Rec	6.00
Rim Alt	5.50 F ; 6 L ; 7 L
ECE	E11-54R-0019046

Load capacity (Kg)

km/h / bar	3.5
90 LS	1120
90 LD	1060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 2:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..