

MULTIMAX MP 527 - Especificaciones técnicas



Description

MULTIMAX MP 527 es un neumático radial polivalente desarrollado para los elevadores telescópicos y las palas compactas que se utilizan en las aplicaciones agro-industriales. El neumático muestra un diseño de bloques de la banda de rodadura, garantizando una excelente tracción hasta en la superficie más dura. El robusto flanco del neumático asegura una extraordinaria estabilidad en modalidad de levantamiento. Además, MULTIMAX MP 527 está realizado con una mezcla particularmente resistente a los cortes y los desgarres, lo cual se traducen en una larga vida operativa del neumático.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Cargadora compacta • Elevador telescópico
Industrial: Cargadora compacta • Elevador telescópico

Version	STANDARD
Type	TL
Tyre Size	440/80 R 28 IND
LI/SS	156 A8/B

Dimensions International Standard

Section Width (mm)	441
Overall Diameter (mm)	1415
Static Loaded Radius (mm)	648
Rolling Circumference (mm)	4270
SRI (mm)	675
Rim Rec	DW 14 L
Rim Alt	DW 13 ; DW 13 L ; DW 15 L
ECE	E11-106R-002984

Load capacity (Kg)

km/h / bar	1.6	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
50	2300	2725	2940	3150	3360	3575	3790	4000	-	-
40	2300	2725	2940	3150	3360	3575	3790	4000	-	-
30	2480	2930	3155	3380	3605	3830	4055	4280	-	-
25	2570	3040	3270	3505	3740	3970	4205	4440	-	-
10 Cyc.	2840	3470	3790	4105	4420	4735	5050	5370	5685	6000
Static	4360	5330	5810	6295	6780	7265	7750	8230	8715	9200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 23:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..