

MULTIMAX MT 518 - Ficha técnica



Description

MULTIMAX MT 518 ha sido específicamente desarrollado para camiones militares. Es un neumático con un dibujo de bloques en la banda de rodadura y cinturones de acero, caracterizado por una elevada resistencia a la perforación, así como una extraordinaria estabilidad. Además, MULTIMAX MT 518 permite que este neumático alcance altas velocidades y asegura un ciclo de vida prolongado.

UM

International Standard

Construction



RADIAL

Machinery

Industrial: Camión militar

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
36 X 12.5 R 16.5	STANDARD	129 N	9.75		315	902	420	2758	TL	E11-54R-0017917

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 0:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..