

PL 801 - Especificaciones técnicas



Description

PL 801 ha sido particularmente desarrollado para los rastrillos hileradores rotativos y los volteadores de heno, así como para las operaciones de logística realizadas con carretillas elevadoras. Este neumático ofrece una excelente estabilidad, así como una elevada resistencia a cualquier tipo de corte. PL 801 asegura un ciclo de vida prolongado del neumático.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Cosechadora • Rastrillo hilerador rotativo •
Carretilla elevadora
Industrial: Carretilla elevadora

Version	STANDARD
Type	TT
Tyre Size	18 X 7 - 8 (180/70 - 8)

Dimensions US Standard

Usa code	94006953
Ply Rating	14
Section Width (inch)	6.8
Overall Diameter (inch)	18.5
Rim Rec	4.33 R
Rim Alt	5.00 F

Load capacity (lbs)

mph / psi	131
15 LOAD WHEEL	4155
15 STEER WHEEL	3195
5 OTHER VEHICLES	4155
15 OTHER VEHICLES	3195
STATIC SIDE LOADER	4830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 17:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..