

## PL 801 - Especificaciones técnicas



### Description

PL 801 ha sido particularmente desarrollado para los rastrillos hileradores rotativos y los volteadores de heno, así como para las operaciones de logística realizadas con carretillas elevadoras. Este neumático ofrece una excelente estabilidad, así como una elevada resistencia a cualquier tipo de corte. PL 801 asegura un ciclo de vida prolongado del neumático.

### UM

US Standard

### Construction

BIAS

### Machinery

Agricultura: Cosechadora • Rastrillo hilerador rotativo •  
Carretilla elevadora  
Industrial: Carretilla elevadora

Version	STANDARD
Type	TT
Tyre Size	250 - 15 (250/70 - 15)

## Dimensions US Standard

Usa code	94007066
Ply Rating	20
Section Width (inch)	9.3
Overall Diameter (inch)	29.3
Rim Rec	7.50 BD
Rim Alt	7.0 ; 7.5

## Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	11110
15 STEER WHEEL	8540
5 OTHER VEHICLES	11110
15 OTHER VEHICLES	8540
STATIC SIDE LOADER	12895

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 7:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..