

## PL 846 - Especificaciones técnicas



### Description

PL 846 ha sido particularmente proyectado para utilizarlo en las máquinas agrícolas que se utilizan para las labores del campo. Este neumático ofrece una extraordinaria estabilidad y una excepcional tracción, así como una elevada resistencia a cualquier tipo de corte. PL 846 es el neumático ideal para todas las superficies rocosas.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Maquinaria agrícola

|           |          |
|-----------|----------|
| Version   | STANDARD |
| Type      | TT       |
| Tyre Size | 6.00 - 9 |

## Dimensions US Standard

|                         |          |
|-------------------------|----------|
| Usa code                | 94035915 |
| Ply Rating              | 12       |
| Section Width (inch)    | 6.3      |
| Overall Diameter (inch) | 21.3     |
| Rim Rec                 | 4.00 E   |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 150  |
| 15        | 3140 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 0:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..