

## PORTMAX PT 93 - Ficha técnica



### Description

PORTMAX PT 93 es el neumático para tractores de terminal y remolques, concretamente fabricado para operaciones de servicio pesadas en las terminales portuarias y en los centros de logística. La banda de rodadura, proyectada con una mezcla especial antiestática, ofrece una particular resistencia al desgaste y al calor incluso en las situaciones más exigentes. PORTMAX PT 93 es el neumático ideal para todas las operaciones que requieran un alto grado de maniobrabilidad, además asegura un grip excelente y una avanzada durabilidad.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrial: Tractor de terminal • Remolque

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	Type
280/75 R 22.5	INDUSTRIAL	94053902	168 A8	8.25	9.00	11.1	39.3	TL
310/80 R 22.5	INDUSTRIAL	94057764	175 A8	9.00		12.1	42.1	TL
315/60 R 22.5	INDUSTRIAL	94067855	170 A8	9.75	9.00	12.1	38	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 12:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..