

POWER TRAX HD SMOOTH - Especificaciones técnicas



Description

POWER TRAX HD SMOOTH es un neumático de telas cruzadas específicamente desarrollado para utilizarlo en las operaciones portuarias y en las minas subterráneas. La especial protección del flanco, así como la sólida banda de rodadura evitan daños causados por cortes y perforaciones, muy comunes en estos ambientes tan difíciles. En el caso de que haya que desplazar cargas pesadas en condiciones duras, Power Trax HD Smooth es el neumático ideal para todas las exigencias.

UM

US Standard

Construction

❖ BIAS

Machinery

Industrial: Manipulador de contenedores • Carretilla elevadora

OTR: Vehículos para minería subterránea

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions US Standard

Usa code	94007882
Ply Rating	20
Section Width (inch)	12.6
Overall Diameter (inch)	45.3
Rim Rec	8.50
Rim Alt	9.0
ECE	E11-106R-005561
Tread Depth	43

Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	20350
15 STEER WHEEL	15650
5 OTHER VEHICLES	20350
15 OTHER VEHICLES	15650
STATIC SIDE LOADER	23630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 6:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..