

POWER TRAX HD - Especificaciones técnicas



Description

El POWER TRAX HD es un neumático de telas cruzadas especialmente diseñado para aplicaciones portuarias y de minería subterránea. Su profunda banda de rodadura y el flanco con un espesor extra, así como su robusta carcasa, se traducen en una extraordinaria durabilidad, minimizando el riesgo de perforación y de daños accidentales. Este neumático se caracteriza por una excelente resistencia a los cortes y las laceraciones, lo que hace que sea especialmente adecuado para superficies rugosas y duras. El borde de protección de la llanta, especialmente diseñado, protege el neumático en el área de la pestaña de la llanta contra desinflamientos y daños.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Manipulador de contenedores

OTR: Vehículos para minería subterránea

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions International Standard

Ply Rating	28
Section Width (mm)	320
Overall Diameter (mm)	1150
Rim Rec	8.50
Rim Alt	9.0
Tread Depth	34

Load capacity (Kg)

km/h / bar	10.00
25 LOAD WHEEL	9490
25 STEER WHEEL	7300
10 OTHER VEHICLES	9490
25 OTHER VEHICLES	7300
STATIC SIDE LOADER	11025

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 6:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..