

PUDDLE SPECIAL (B) - Especificaciones técnicas



Description

PUDDLE SPECIAL es un neumático agrícola R-2 particularmente desarrollado para utilizarlo en los arrozales. El diseño extra profundo de la banda de rodadura, además de la disposición especial de los tacos, asegura una óptima adherencia y una excelente tracción incluso en terrenos húmedos y blandos. El amplio elemento central ofrece una mejor capacidad de adaptación para las aplicaciones por carretera, así como excelentes prestaciones operativas. Además, PUDDLE SPECIAL muestra óptimas propiedades de auto-limpieza y una elevada duración.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Pulverizador

Version	STANDARD
Type	TT
Tyre Size	120/90 - 26
LI/SS	90 A2

Dimensions International Standard

Ply Rating	6
Section Width (mm)	127
Overall Diameter (mm)	940
Static Loaded Radius (mm)	448
Rolling Circumference (mm)	2847
Rim Rec	4 JA
ECE	E11-106R-005236

Load capacity (Kg)

km/h / bar	3.00
10	600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 2:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..