

RIB 713 - Especificaciones técnicas



Description

RIB 713 es un neumático con cinturones de acero utilizado en las máquinas agrícolas. Como respuesta al aumento de la conciencia sobre el tema de la baja compactación del suelo en la agricultura moderna, RIB 713 se ha desarrollado con la tecnología IF. Por lo que este neumático puede sostener cargas más pesadas con una presión de inflado inferior, presentando una huella más ancha y una distribución uniforme del peso. La estructura con cinturones de acero garantiza una extraordinaria resistencia a la perforación y una mayor protección contra la penetración de tallos y sus consecuentes daños, incluso en presencia de rastrojos insidiosos. Además, la categoría velocidad "D" (65 km/h – 40 mph) permite desplazarse rápidamente por la carretera. RIB 713 es la contribución de BKT para maximizar la productividad y la eficiencia de su empresa agrícola.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Maquinaria agrícola

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	IF 280/70 R 15
LI/SS	134 D

Dimensions International Standard

TKPH	1
Section Width (mm)	279
Overall Diameter (mm)	779
Static Loaded Radius (mm)	347
Rolling Circumference (mm)	2356
SRI (mm)	360
Rim Rec	W 8
ECE	E11-106R-005094
TRA Code	I1

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
From 10 to 65 km/h	775	885	1010	1120	1225	1335	1425	1570	1695	1800	1995	2120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 4:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..