

RIB 774 (C) - Especificaciones técnicas



Description

RIB 774 (C) es un neumático de sección baja con base estrecha (narrow) para maquinaria agrícola. Este neumático es ideal para aplicaciones de recogida de heno y de transporte con empacadoras de heno y remolques por carretera y fuera de carretera. Este neumático asegura una capacidad elevada de carga y un amplio ciclo de vida del producto.

UM

US Standard

Construction



Machinery

Agricultura: Empacadora de heno • Cosechadora • Remolque

| | |
|---------------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 225/75 - 17.5 |
| LI/SS FREE ROLLING | 134 A8 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94011025 |
| Ply Rating | 12 |
| Section Width (inch) | 8.7 |
| Overall Diameter (inch) | 30.5 |
| Static Loaded Radius (inch) | 14.2 |
| Rolling Circumference (inch) | 90.9 |
| Rim Rec | 6.75 |

ECE E11-106R-004657

Load capacity (lbs)

| mph / psi | 100 |
|-----------|------|
| 5 FR | 6550 |
| 15 FR | 5570 |
| 20 FR | 5240 |
| 25 FR | 4670 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 15:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..