

RIB 900 - Especificaciones técnicas



Description

RIB 900 es un neumático idóneo para el transporte, los trabajos del campo y la recogida de heno con remolques, maquinaria agrícola y empacadoras de heno. Este neumático asegura una capacidad elevada de carga y un amplio ciclo de vida del producto.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora •
Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	147 A8

Dimensions International Standard

Ply Rating	16
Section Width (mm)	405
Overall Diameter (mm)	875
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2564
Rim Rec	AG 13.00
ECE	E4-106R-001548

Load capacity (Kg)

km/h / bar	4.00
10 FR	4305
25 FR	3660
30 FR	3445
40 FR	3075

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 15:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..