

RIB 900 - Ficha técnica



Description

RIB 900 es un neumático idóneo para el transporte, los trabajos del campo y la recogida de heno con remolques, maquinaria agrícola y empacadoras de heno. Este neumático asegura una capacidad elevada de carga y un amplio ciclo de vida del producto.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora •
Maquinaria agrícola • Remolque

SIZE	Version	USACode	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
400/60 - 15.5	STANDARD	94026357	139 A8	10	AG 13.00		15.9	34.4	15	100.9	TL	
400/60 - 15.5	STANDARD	94026173	145 A8	14	AG 13.00		15.9	34.4	15	100.9	TL	E4-106R-001551
400/60 - 15.5	STANDARD	94026340	147 A8	16	AG 13.00		15.9	34.4	15	100.9	TL	E4-106R-001548

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 7:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..