

RIB TRAILER - Ficha técnica



Description

El RIB TRAILER es un neumático diagonal diseñado especialmente para aplicaciones en carretera, pero también todoterreno con aperos remolcados, especialmente cosechadoras de paja. Su diseño con 4 costillas optimiza la distribución de la carga y la robusta carcasa garantiza resistencia contra los rastrojos. El RIB TRAILER se ha diseñado con un compuesto especial que asegura una excelente vida útil del neumático gracias a su elevada resistencia al desgaste.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricultura: Maquinaria agrícola

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type
6.00 - 16	STANDARD	94 A6	8	4.50 E	4.00 E ; 5 K ; 5.00 F	170	735	TT
7.00 - 19	STANDARD	119 A3	10	5.00		210	875	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 7:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..