

RIDEMAX FL 615 - Especificaciones técnicas



Description

RIDEMAX FL 615 es un neumático de flotación radial ideal para ejes no motrices de remolques, camiones cisterna y esparcidores. La estructura con cinturones de acero ofrece una alta resistencia a las perforaciones con mayor durabilidad y alta capacidad de carga. RIDEMAX FL 615 proporciona una baja resistencia al rodamiento en carretera con excelentes propiedades de autolimpieza en el campo. Su hombro redondeado y la amplia área de huella garantizan una óptima protección del suelo.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

Version	STEEL BELTED
Type	TL
Tyre Size	VF800/65 R 32
LI/SS	190 D
LI/SS DRIVE WHEEL	190 D
LI/SS FREE ROLLING	190 D

Dimensions International Standard

Section Width (mm)	815
Overall Diameter (mm)	1850
Static Loaded Radius (mm)	811
Rolling Circumference (mm)	5610
SRI (mm)	875
Rim Rec	DW 28 B
ECE	E11-106R-0010408

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8
65	5195	5830	7105	8060	9330	10600
50	6080	6825	8315	9430	10920	12405
40	6705	7525	9165	10395	12035	13675
30	7330	8225	10020	11365	13160	14950
25	7590	8515	10375	11765	13625	15480
20	7900	8865	10800	12250	14185	16115
10	8520	9565	11650	13215	15300	17385

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 15:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..