

## RIDEMAX FL 690 - Especificaciones técnicas



### Description

RIDEMAX FL 690 es un neumático radial de flotación y transporte, idóneo para utilizarlo con remolques y autocisternas. El neumático es idóneo para utilizarlo 75% por carretera. Para responder a la necesidad de cargas cada vez más pesadas en la agricultura moderna, BKT ha diseñado este neumático con cinturones de acero, haciéndolo más fuerte con el fin de soportar cargas muy pesadas e incrementando la productividad del agricultor. La baja resistencia de al rodamiento contribuye a reducir los consumos de carburante.

### UM

International Standard

### Construction



RADIAL

### Machinery

Agricultura: Camión cisterna • Remolque

Industrial: Remolque

|           |                           |
|-----------|---------------------------|
| Version   | STANDARD                  |
| Type      | TL                        |
| Tyre Size | 28L R 26<br>(750/65 R 26) |
| LI/SS     | 176 A8/173 B              |

# Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 719             |
| Overall Diameter (mm)      | 1590            |
| Static Loaded Radius (mm)  | 695             |
| Rolling Circumference (mm) | 4745            |
| SRI (mm)                   | 750             |
| Rim Rec                    | DW 25 B         |
| Rim Alt                    | DW 23 B         |
| ECE                        | E11-106R-002985 |

## Load capacity (Kg)

| km/h / bar | 0.8  | 1.0  | 1.4  | 1.6  | 2.0  | 2.4  | 2.8  |
|------------|------|------|------|------|------|------|------|
| 50         | 3120 | 3560 | 4325 | 4680 | 5330 | 5915 | 6500 |
| 40         | 3410 | 3885 | 4725 | 5115 | 5825 | 6465 | 7100 |
| 30         | 3820 | 4355 | 5295 | 5730 | 6525 | 7240 | 7955 |
| 25         | 4060 | 4625 | 5620 | 6085 | 6930 | 7690 | 8450 |
| 10         | 4775 | 5440 | 6615 | 7160 | 8155 | 9050 | 9940 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 16:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..