

RIDEMAX FL 690 - Especificaciones técnicas



Description

RIDEMAX FL 690 es un neumático radial de flotación y transporte, idóneo para utilizarlo con remolques y autocisternas. El neumático es idóneo para utilizarlo 75% por carretera. Para responder a la necesidad de cargas cada vez más pesadas en la agricultura moderna, BKT ha diseñado este neumático con cinturones de acero, haciéndolo más fuerte con el fin de soportar cargas muy pesadas e incrementando la productividad del agricultor. La baja resistencia al rodamiento contribuye a reducir los consumos de carburante.

UM

International Standard

Construction



RADIAL

Machinery

Agricultura: Camión cisterna • Remolque

Industrial: Remolque

Version	STANDARD
Type	TL
Tyre Size	30.5L R 32
LI/SS	184 A8/181 B

Dimensions International Standard

Section Width (mm)	790
Overall Diameter (mm)	1800
Static Loaded Radius (mm)	806
Rolling Circumference (mm)	5430
SRI (mm)	875
Rim Rec	DH 27 B
Rim Alt	DW 27 B
ECE	E11-106R-002986

Load capacity (Kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.0
50	3795	4375	5280	5695	6520	7260	7920	8250
40	4370	5030	6075	6550	7500	8355	9115	9490
30	4935	5685	6865	7405	8475	9440	10300	10725
25	5205	5995	7240	7805	8935	9950	10855	11305
10	6040	6955	8400	9055	10365	11550	12600	13120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 16:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..