

RIDEMAX FL 693 M - Especificaciones técnicas



Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	750/60 R 30.5
LI/SS	181 D

Dimensions US Standard

Usa code	94033812
Section Width (inch)	29.7
Overall Diameter (inch)	65.9
Static Loaded Radius (inch)	28.7
Rolling Circumference (inch)	200.5
Rim Rec	AG 24.00
ECE	E4-106R-001499

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	6130	6960	8450	9780	11260	12750	13750	15230	16560
40	6730	7640	9280	10740	12370	14010	15100	16730	18190
30	8160	9250	11230	13000	14970	16950	18280	20260	22010
25	9160	10390	12620	14590	16820	19050	20530	22760	24730
15	10640	12070	14660	16960	19540	22130	23850	26440	28740
5	12120	13760	16700	19320	22270	25210	27180	30120	32740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 16:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..