

RIDEMAX IT 696 - Especificaciones técnicas



Description

RIDEMAX IT 696 se caracteriza por un único dibujo de la banda de rodadura y una huella amplia que proporcionan un excelente agarre en la carretera, incluso en condiciones invernales. El neumático se presta especialmente para las actividades de los medios municipales y de mantenimiento, gracias a las óptimas características de velocidad y la carcasa robusta. El dibujo de la banda de rodadura ha sido desarrollado especialmente para los trabajos más pesados y garantiza una baja resistencia al rodamiento que se traduce en ahorro de carburante y excelente estabilidad.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 420/65 R 24 IND |
| LI/SS | 146 D/151 A8 |

Dimensions US Standard

| | |
|------------------------------|-------------------|
| Usa code | 94058464 |
| TMPH | 1 |
| Section Width (inch) | 16.5 |
| Overall Diameter (inch) | 45.6 |
| Static Loaded Radius (inch) | 20.9 |
| Rolling Circumference (inch) | 137.1 |
| Rim Rec | DW 13 L; W13 |
| Rim Alt | DW 15 L ; DW 14 L |
| ECE | E11-106R-005952 |

Load capacity (lbs)

| mph / psi | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|------|------|------|------|
| 40 | 2650 | 3240 | 3640 | 4300 | 4890 | 5490 | 6020 | 6610 |
| 30 | 2850 | 3510 | 3920 | 4640 | 5290 | 5930 | 6500 | 7140 |
| 25 | 3040 | 3730 | 4190 | 4950 | 5630 | 6320 | 6920 | 7610 |
| 20 | 3170 | 3890 | 4360 | 5160 | 5870 | 6590 | 7220 | 7940 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 14:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..