

RIDEMAX IT 696 - Especificaciones técnicas



Description

RIDEMAX IT 696 se caracteriza por un único dibujo de la banda de rodadura y una huella amplia que proporcionan un excelente agarre en la carretera, incluso en condiciones invernales. El neumático se presta especialmente para las actividades de los medios municipales y de mantenimiento, gracias a las óptimas características de velocidad y la carcasa robusta. El dibujo de la banda de rodadura ha sido desarrollado especialmente para los trabajos más pesados y garantiza una baja resistencia al rodamiento que se traduce en ahorro de carburante y excelente estabilidad.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	440/80 R 34 IND (16.9 R 34)
LI/SS	159 A8/155 D

Dimensions International Standard

Section Width (mm)	441
Overall Diameter (mm)	1567
Static Loaded Radius (mm)	704
Rolling Circumference (mm)	4775
SRI (mm)	750
Rim Rec	DW 14 L
Rim Alt	DW 15 L; DW 16 L
ECE	E4-106R-002295

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1820	2250	2635	3060	3450	3875
50	1935	2390	2800	3255	3665	4120
40	2055	2540	2975	3455	3895	4375
30	2145	2645	3100	3600	4060	4560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 18:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..