

RM 2002 - Ficha técnica



Description

RM 2002 es un neumático idóneo para las operaciones de transporte con remolques y furgonetas tanto por carretera como fuera de carretera. Este neumático asegura una larga durabilidad y elevadas prestaciones durante todo el ciclo de vida del producto. Su versión "industrial" es ideal para las grúas móviles "pick & carry".

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Remolque

Industrial: Grúa móvil

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
11.00 - 20	INDUSTRIAL	94035120	18	8.0	7.5 ; 8.5	11.9	43.3	0	0	TT
11.00 - 20	INDUSTRIAL	94027200	16	8.0	7.5 ; 8.5	11.9	43.3	0	0	TT
11.00 - 20	STANDARD	94022656	16	8.0	7.5 ; 8.5	11.9	43.3	0	0	TT
11.00 - 20	STANDARD	94064908	18	8.0	7.5 ; 8.5	11.9	43.3	0	0	TT
12.00 - 20	STANDARD	94022687	18	8.5	8.0 ; 9.0	12.4	45.1	21	139.3	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 6:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..