

## ROCK GRIP E4 - Especificaciones técnicas



### Description

ROCK GRIP (E-4) es un neumático de telas cruzadas especialmente proyectado para los camiones que se utilizan en las minas y las canteras. ROCK GRIP es el neumático ideal cada vez que las condiciones operativas para realizar transportes cortos en el sitio de trabajo requieran tanto resistencia al calor como protección a los cortes.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Dúmpers rígidos

|           |            |
|-----------|------------|
| Version   | STANDARD   |
| Type      | TT         |
| Tyre Size | 18.00 - 25 |

# Dimensions International Standard

|                            |           |
|----------------------------|-----------|
| Ply Rating                 | 32        |
| Overall Width (mm)         | 510       |
| Overall Diameter (mm)      | 1650      |
| Static Loaded Radius (mm)  | 753       |
| Rolling Circumference (mm) | 4885      |
| Rim Rec                    | 13.00/2.5 |
| Rim Alt                    | 15.00/2.5 |
| TRA Code                   | E4        |
| Tread Depth                | 54        |

## Load capacity (Kg)

| km/h / bar | 5.75 | 7.50  |
|------------|------|-------|
| 50         | 8750 | -     |
| 10         | -    | 15000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 11:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..