

## RT 857 - Especificaciones técnicas



### Description

RT 857 es un neumático idóneo para la aplicaciones de los trabajos del campo. Su robusta carcasa garantiza un excelente durabilidad y optimá tracción. La mezcla de la banda de rodadura se caracteriza por una elevada resistencia a cualquier tipo de corte y de rastrojo.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	460/85 R 26 (18.4 R 26)
LI/SS	143 A8/B

## Dimensions International Standard

Section Width (mm)	465
Overall Diameter (mm)	1442
Static Loaded Radius (mm)	642
Rolling Circumference (mm)	4297
SRI (mm)	675
Rim Rec	DW 15 L
Rim Alt	W 15 L ; W 16 L ; DW 16 L
ECE	E4-106R-001479
TRA Code	R1

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1500	1745	1990	2235	2480	2725
40	1500	1745	1990	2235	2480	2725
30	1610	1870	2135	2395	2660	2920
10LT	2015	2340	2670	3000	3330	3655
10HT	1610	1870	2135	2395	2660	2920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 1:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..