

SKID POWER HD (B) - Ficha técnica



Description

SKID POWER HD (B) ha sido proyectado para las minicargadoras (**skid steer**) que se utilizan en el sector de la construcción. Este neumático se caracteriza para la banda de rodadura extra profunda y la protección de los flancos, asegurando una excelente resistencia a los cortes y los desgarres, así como una extraordinaria duración. SKID POWER HD (B) es el neumático ideal para las superficies terrosas y los trabajos más pesados.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Minicargadora compacta

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.5 - 10	IMPLEMENT	82 A8	8	7.00 I - 55 ; I - 70 ; I - 90		205	465	213	1372	TL	E11-106R-003536
18 X 8.5 - 10	STANDARD	96 A2	8	7.00 I - 55 ; I - 70 ; I - 90		205	465	211	1393	TL	E11-106R-006774

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..