

SKID POWER HD (B) - Ficha técnica



Description

SKID POWER HD (B) ha sido proyectado para las minicargadoras (**skid steer**) que se utilizan en el sector de la construcción. Este neumático se caracteriza para la banda de rodadura extra profunda y la protección de los flancos, asegurando una excelente resistencia a los cortes y los desgarres, así como una extraordinaria duración. SKID POWER HD (B) es el neumático ideal para las superficies terrosas y los trabajos más pesados.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Minicargadora compacta

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.5 - 10	IMPLEMENT	94055937	82 A8	8	7.00 I - 55 ; I - 70 ; I - 90		8.1	18.3	8.4	54	TL	E11-106R-003536
18 X 8.5 - 10	STANDARD	94017751	96 A2	8	7.00 I - 55 ; I - 70 ; I - 90		8.1	18.3	8.3	54.8	TL	E11-106R-006774

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..