

SKID POWER SK - Especificaciones técnicas



Description

SKID POWER SK ha sido desarrollado particularmente para las minipalas cargadoras (skid steer) que se utilizan en el sector de la construcción. Los cordones de protección del flanco y de la llanta, así como la banda de rodadura extra profunda proporcionan un ciclo de vida prolongado del neumático.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Minicargadora compacta

Version	IMPLEMENT
Type	TL
Tyre Size	10 - 16.5
LI/SS	120 A8

Dimensions US Standard

Usa code	94055715
Ply Rating	10
Section Width (inch)	10.6
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14
Rolling Circumference (inch)	90
Rim Rec	8.25
Rim Alt	
ECE	E11-106R-003544

Load capacity (lbs)

mph / psi	75
25	3085

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 14:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..