

SM 53 - Ficha técnica



Description

SM 53 ha sido específicamente desarrollado para las cargadoras que se utilizan en las minas subterráneas y en las operaciones de carga. Este neumático se caracteriza por una elevada estabilidad y por el dibujo liso de la banda de rodadura, proporcionando una excelente resistencia a los cortes.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Vehículos para minería subterránea

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
9.00 - 20	STANDARD	L3S	16	7.0		266	1040	472	3080	TT	23

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 5:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..