

SM 54 IND-4S - Especificaciones técnicas



Description

El SM 54 IND-4S se ha diseñado específicamente para las máquinas que se utilizan en la manipulación de los contenedores vacíos y para las grúas reach stacker utilizadas en las operaciones intermodales y logísticas. Este neumático se caracteriza para una elevada estabilidad en la modalidad de levantamiento, así como por el profundo dibujo liso de la banda de rodadura, que garantiza una excelente resistencia a los cortes y asegura un ciclo de vida prolongado.

UM

International Standard

Construction

❖ BIAS

Machinery

Industrial: Grúa Reach Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	430
Overall Diameter (mm)	1470
Static Loaded Radius (mm)	676
Rolling Circumference (mm)	4354
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	L4S

Load capacity (Kg)

km/h / bar	9.00
10	15525

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 15:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..