

SNOW GRIP - Especificaciones técnicas



Description

SNOW GRIP está especialmente proyectado para las carretillas elevadoras que operan en ambientes a bajas temperaturas. El dibujo único de la banda de rodadura se caracteriza por unos bordes especiales que garantizan un agarre superior sobre la nieve fresca y compacta, asegurando además excelentes prestaciones en las curvas y en el frenado sobre superficies heladas y nevadas. La estructura de doble talón, su robusta carcasa y la particular protección de los flancos proporcionan una elevada capacidad de carga, una excelente estabilidad y maniobrabilidad en la modalidad de levantamiento, así como prolongado el ciclo de vida del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Carretilla elevadora

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	131 A2

Dimensions International Standard

Ply Rating	12
Section Width (mm)	210
Overall Diameter (mm)	810
Rim Rec	6.0

Load capacity (Kg)

km/h / bar	5.0
10	1950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 16:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..