

SNOW - RIDE (A) - Especificaciones técnicas



Description

SNOW-RIDE es específicamente idóneo para las aplicaciones de municipalidad/mantenimiento que se realizan en condiciones invernales con cargadoras compactas y minicargadoras compactas. Este neumático se caracteriza para su excelente tracción y es ideal para los trabajos realizados en la nieve y el hielo. El dibujo especial de la banda de rodadura elimina los riesgos de derrape asegurando un ciclo de vida prolongado del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Cargadora compacta
Industrial: Minicargadora compacta

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	270
Overall Diameter (mm)	780
Static Loaded Radius (mm)	357
Rolling Circumference (mm)	2340
Rim Rec	8.25

Load capacity (Kg)

km/h / bar	5.20
10	2135

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 14:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..