

## STEER FARM - Especificaciones técnicas



### Description

STEER FARM ha sido proyectado para los tractores 2WD/2RM que se utilizan en los trabajos del campo, asegurando un excelente comportamiento de la dirección.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Tractor 2WD

Version	STANDARD
Type	TT
Tyre Size	6.50 - 20
LI/SS	93 A8

## Dimensions US Standard

Usa code	94043736
Ply Rating	8
Section Width (inch)	7.7
Overall Diameter (inch)	34.6
Static Loaded Radius (inch)	16.5
Rolling Circumference (inch)	106.3
Rim Rec	5.50 F
Rim Alt	4.00 E ; 5.00 F
ECE	E4-106R-002833
TRA Code	F2

## Load capacity (lbs)

	mph / psi	66
	25	1440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..